



MODEL NUMBER: 11L-S-MVS1-DF-400F

Wiring Configurations

	480/277	208/120	240/120	240/120
Rated Voltage	480/277	208/120	240/120	240/120
Winding Configuration	Hi-Wye	Lo-Wye	Delta	Zig Zag
Phase	3	3	3	1
Prime Power	170 kW 212 kVA	170 kW 212 kVA	170 kW 212 kVA	92 kW 115 kVA
Rated Amps	255	589	511	479

Fuel Consumption*

Load %	NG Rating	LP Rating
100%	1,974,456 Btu/hr	1,571,514 Btu/hr
75%	1,544,200 Btu/hr	1,236,642 Btu/hr
50%	1,130,118 Btu/hr	917,954 Btu/hr
25%	732,208 Btu/hr	615,449 Btu/hr

Genset Information

Voltage	480 V
Frequency	60 Hz
NG PRP Rating	170 kW 212 kVA
LP PRP Rating	125 kW 156 kVA
Wet Weight	10,929 lbs

Engine Information

Model	PSI 11.1L
Nameplate Rating	200 kW 268 hp
Speed	1,800 rpm
Displacement	11.1 L 673 in ³
Cylinder Arrangement	6 Cylinders Inline
Aspiration Mode	Turbocharged

* NG: HHV=1,041 Btu/scf (39 MJ/m³)
LP: HHV=2,538 Btu/scf (95 MJ/m³)

Control System

Controller Type	DSE 8610 MKII
Synchronizing & Load Sharing	Yes
Telemetry & Remote Monitoring	Yes

Emission Control

AFR Controller	Yes
NSCR Catalyst	Yes

Alternator

Manufacturer	Stamford
Model	UCI274J Wdg. 311
Rated Power Factor	0.8 PF
Rating	240 kW 300 kVA
Excitation Type	PMG
Insulation Class	Class H
Temp. Rise / Ambient	125 / 40°C
Enclosure	IP23